



Door and glass frames are face-flush with the closed wall elements and separated by 6 mm shadow joints. The only exceptions to this wall thickness are the recessed-designed fecoplan glazings and the special design variants with wall thicknesses of 125 mm and 175 mm respectively for exceptional static and acoustic requirements.

All fastenings are concealed as standard. Screw connections or other point connections are not visible, neither in the closed wall elements nor in glass walls. Connections to the floor, wall and ceiling have recessed shadow joints. The ceiling connection has a standard telescopic design to accommodate construction tolerances and structural movements.

One special aspect of the feco partition wall system is the way in which the wall panels are connected to the substructure. In the patented feco clamping system, wall panels are clipped into the system uprights using the full-length, reverse-mounted steel retaining rails. This method provides more stability, more accurate joint alignment and increased sound insulation values compared to structures with only point fixture. The wall panels contribute to high static strength across their entire surface area, while the slim system uprights reduce the transmission of sound waves.

Wall heights of up to 5.000 mm, sound insulation values up to  $R_{w,P} = 52$  dB, and fire resistance ratings up to 90 minutes with a uniform wall thickness of 105 mm are possible, as proven by numerous test reports, test certificates and approvals.

Please contact us for more information on how we can individually meet your specific requirements.

feco partition wall systems are as individual as your project. System partition walls are lightweight, non-load-bearing, unitized and removable interior walls with closed and transparent surfaces made of wood, glass and metal. They consist of a metal substructure and two-sided cladding with intermediate insulation as well as glazings and doors. The wall elements are prefabricated building-specific at the factory and assembled on site in short, clean assembly processes.

feco system partition walls meet the highest construction-related requirements in terms of sound insulation, sound absorption, fire protection and statics. Add to this, the wide-ranging design options. In addition to a wide variety of surfaces, the feco system offers a wide range of glazing constructions for every requirement and every taste.

The big advantage of the system partition walls is their relocatability. In conjunction with an element system matched to the building grid, rooms can be subsequently adapted to requirements, walls installed and removed or doors exchanged for wall elements. If desired, even during ongoing business operations. The additional investment compared to drywall walls usually pays for itself with the first conversion measure.

The partition wall elements - whether solid wall, glazing or door units - all have a basic wall thickness of 105 mm.

## feco product overview

Product	Detail	Description	Wall thickness	Panel/Glass/Door leaf thickness	Visible width vertical/horizontal	Sound insulation test values $R_{w,P}$	Fire resistance
fecowand		Solid wall	105 mm	2 x 19 mm	-	47-52 dB	EI30 EI90
fecowand		Solid wall in special thickness	125 mm 175 mm	2 x 19 mm	-	47-57 dB	EI30
fecoorga		Wall organisation	105 mm	2 x 19 mm	-	45-52 dB	EI30 EI90
fecophon		Acoustic solid wall	105 mm	2 x 19 mm	-	27-49 dB	-
fecoplan		All-glass construction	35 mm	10-18 mm	0/50 mm	35-42 dB	-
fecocent		Wall-centered glazing	105 mm	8 mm 28 mm	35/35 mm	32-37 dB 37-42 dB	G30 F30
fecofix		Wall-flush glazing	105 mm	1 x 5-8 mm 2 x 5-8 mm	20/20 mm	32-37 dB 39-49 dB	F30
fecostruct		Face-flush glazing	105 mm	1 x 6-8 mm 2 x 6-8 mm	20/20 mm	32-37 dB 39-47 dB	-
fecotür Wood		Wooden doors	105 mm	40-105 mm	18-50 mm	23-42 dB	T30
fecotür Glass		Glassdoors	105 mm	10 mm 40-105 mm	18-50 mm	23-32 dB 32-42 dB	-

The feco partition wall system is constantly being further developed. Ask us about the latest innovations.